

J2 Feedback

TDM Transponder

TransCore's J2 Feedback TDM Transponder is a 915-MHz battery powered radio frequency identification (RFID) transponder. It is ideal for high-speed, high-reliability applications.

A multi-color (red, green, and yellow) light emitting diode (LED) and audible buzzer alerts drivers of tolling transactions and notifications. The transponder responses are determined by the issuing agency.

The J2 Feedback TDM transponder works for basic IAG operations and includes the capability to detect and prevent transponder tampering, cloning, and spoofing.

The J2 Feedback TDM Transponder's case is constructed of highly durable, impact resistant, molded plastic. The non-replaceable internal battery provides years of maintenance-free service.

The J2 Feedback TDM Transponder is designed for mounting to a vehicle's interior windshield with suction cups or hook-and-loop fastener strips for easy installation and removal.

Other customizable options include printing on the case, molded insert on the front of the case, custom case colors, and laser-etching.



Features

- ▶ High speed, high performance reading and writing
- ▶ Capability to detect and prevent transponder tampering, cloning, and spoofing
- ▶ Visual and audio indicators
- ▶ Non-replaceable internal battery with a 7.5-year design life
- ▶ Mounts to interior windshield with suction cups or hook-and-loop fastener strips
- ▶ Impact resistant, molded plastic case available in six colors: blue, white, yellow, green, orange, and gray
- ▶ Custom printing available on front and back of case

Applications

- ▶ Electronic toll collection
- ▶ Traffic management

J2 Feedback TDM Transponder

COMMUNICATIONS

Transmit Frequency Range

915 MHz (nominal center)

Trigger/Receive Frequency

915.75 MHz (nominal center)

Polarization

Linear, horizontal

SOFTWARE FEATURES

Data Memory

256 bits

IAG-TDM

Data Rate

500 kb/s Manchester

Data Format

Manchester keyed carrier

Error Checking

16-bit cyclic redundancy check (CRC)

POWER

Power Source

Internal lithium battery

LIFE EXPECTANCY

Service Life

7.5-year design life

PHYSICAL CHARACTERISTICS

Weight

1.75 oz. (49.61 g)

Dimensions

4.35 x 1.42 x 0.56 in (11.05 x 3.61 x 0.42 cm)

Color

Six colors: white, blue, orange, yellow, green, and gray

Audio/Visual (A/V) Indicators

One multi-color (red, green, and yellow) light emitting diode (LED) and audible buzzer. When used in normal road tolling applications, the indicators provide driver feedback regarding account status.

Case

Plastic cases are UV stable and are not affected by temperature extremes or severe conditions typical of this operating environment. Shock and vibration resistant.

Mounting Surface

Interior: Non-metallic windshield

Mounting Method

Suction cupps or hook-and-loop fastener strips

ENVIRONMENTAL

Operating Temperature

-40°F to +185°F (-40°C to +85°C)

Humidity

100% condensing

REGULATORY

Complies with Part 15 of the FCC rules

FCC ID: FIH051132B

IC ID: 1584A-FIH051132B

COMPATIBILITY

TDM

MODEL PART NUMBERS

13-7822-NNN

For more information:

Sales Support

800.923.4824

Technical Support

505.856.8007

[transcore.com](https://www.transcore.com)

